



Technical requirements:

- 1)Surface: Nickel plated
- 2)Working Temperature:-10°C~80°C
- 3)Max pressure:DN15(1/2")-DN25(1") max.20bar,
DN32(1 1/4")-DN50(2") max.16bar
- 4)Threaded ends: ISO 228

| NO. | Part name | Material | PR I ND | 8900780 | 8900781 | 8900782 | 8900783 | 8900784 | 8900785 |
|-----|-------------|----------|---------|---------|---------|---------|---------|---------|---------|
| | | | 1 | Body | CW617N | DN1 | 1/2 | 3/4 | 1 |
| 2 | Bonnet | CW617N | DN2 | 1/2 | 3/4 | 1 | 1 1/4 | 1 1/2 | 2 |
| 3 | Ball | CW617N | φ | 14.5 | 19 | 24 | 31 | 38 | 49 |
| 4 | PTFE seat | PTFE | I 1 | 13 | 13 | 15.5 | 18 | 18 | 19 |
| 5 | Stem | CW617N | I 2 | 13 | 13 | 15.5 | 18 | 18 | 19 |
| 6 | O-ring | EPDM | L | 53.5 | 59 | 69.5 | 83 | 91.5 | 112 |
| 7 | Packing nut | CW617N | H | 86 | 89 | 92 | 111 | 111 | 123 |
| 8 | Handle | Steel | L1 | 85.5 | 85.5 | 97 | 118 | 138 | 160 |
| 9 | Screw | S. S | PN | 20 | | | | | |



GmbH

Code

JL-7520

Description